PAITENT

Docke: No: ST00025USU (SIRF.123USU1)

Serial No.: 09/967.136

CLAIMS

1(Currently Amended). A method for reducing the number of calculations required to correlate an incoming spread spectrum signal received by a GPS receiver and encoded with a pseudorandom code, comprising:

determining, for the spread spectrum signal, mathematical processes that are repeated in a correlation process;

removing at least a portion of the mathematical processes that are repeated in the correlation process and results in remaining mathematical processes in the correlation process;

storing the remaining mathematical processes in at least one a table; and

using the <u>at least one</u> table during the correlation process to determine when a locally generated pseudorandom code and the incoming pseudorandom code received at the GPS receiver are correlated where the <u>at least one</u> table accounts for signal phase inversion is constructed for one of the terms of the spread spectrum signal.

2.(Original) The method of claim 1, wherein the mathematical processes are partial accumulations.

3.(Original) The method of claim 2, wherein a portion of the locally generated code and a portion of the incoming pseudorandom code are used to determine correlation of the locally generated code and the incoming pseudorandom code.

PATENT

Docke: No: ST00025USU (SIRF.123USUI)

Serial No.: 09/967,136

4.(Original) The method of claim 3. wherein the incoming spread spectrum signal is a Satellite Positioning System (SATPS) signal.

5.(Original) The method of claim 4, wherein the SATPS signal is a Global Positioning System (GPS) signal.

6.(Original) The method of claim 5, wherein the table is addressed using at least one data bit of the GPS signal and at least one associated code bit of the GPS signal.

7.(Original) The method of claim 6, wherein the at least one associated code bit is at least four associated code bits, and the at least one data bit is at least four data bytes.

8.(Original) The method of claim 7, wherein the data bytes are represented by In-phase (I) and Quadrature phase (Q) forms.

9-16.(Cancelled)